3" INGROUND 120V

5032



LANDSCAPE LIGHTING







Fixture Type:	
Catalog Numbe	er:
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape Wall Wash luminaire

FEATURES

- Adjustable beam angle
- Integral dimmer
- IP67 rated, protected from temporary immersion under water
- Drive over up to 4500lbs
- Solid diecast brass or corrosion resistant aluminum
- Available concrete pour kit
- 6' lead wire and wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1598 listed
- Not suitable to use with external dimmers

SPECIFICATIONS

 Input:
 110V - 120VAC

 Power:
 3W to 11.5W

 Brightness:
 65 lm to 515 lm

 Beam Angle:
 15° to 60°

 CRI:
 85

 Rated Life:
 45,000 hours

IEC safety Standard	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496KN)
Resistance to torque and shear loads test	N/A	Yes


ORDERING NUMBER

		Color Temp		Finish	
5032	3" Inground 120V	30	3000K	BZ BBR	Bronze on Aluminum Bronze on Brass

5032-30

Example: 5032-30BBR










Adjust Beam Angles Presets at 15°, 30°, 45°, 60°



Adjustable WAC Inground
Adjust the light to where you need it







Control Brightness Adjustable from 65lm to 515lm Presets Comparable to 10W, 25W, 35W, 50W, 75W Halogen source



Rock Guard

Protects the fixture face



5030-GRD-BZ Bronze on Aluminum

5030-GRD-BBR Bronze on Brass

Optics

Enhances saturation of florals and foliage



LENS-25-AMB Amber

LENS-25-RED

LENS-25-FR

Red

Frosted

LENS-25-GRN Green

LENS-25-BLU Blue

LENS-25-HCL

Honeycomb Louver Reduces glare

Concrete Pour Kit

For installation in concrete Five ½" NPT threaded holes, PC

5030-PIP-PVC

Shown with temporary dense foam cap



