

1633 Staunton Ave Los Angeles, CA 90021

TEL.

(800) 727-9957

(800) 727-9262 (213) 747-4500

(213) 747-3234



SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

PRODUCT #: CL-201-AB

**Fixture Specifications:** 

**Housing:** Cast Brass fixture mounted with stainless steel

retention clips inside PVC sleeve.

Face Plate Finish: AB- Antique Bronze.

Natural toning process. AB finish will vary due to artistic process.

Lens: Clear, tempered and heat resistant convex glass.

Extra flat lens included.

Socket: Top grade ceramic bi-pin socket with retention

Lamp: 12V, MR-16 halogen, 50W max. L-BAB-C20 (20w)

standard. See below for available LED lamps.

Gasket: Silicone "0" ring seals faceplate to housing

providing weather tight protection.

•Well Lights

Wiring: Fixture is prewired with a 3-ft 18-2 SJT-W direct

Cast Brass

burial cord. Wire connector available seperately.

Gel filled wire nut CX-854 may be ordered to

Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.


Electrical Notes: A remote 12V transformer required, may be


ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V Voltage range for LED lamps are 9V-17V.

Warranty: Limited lifetime warranty on brass fixture

against manufacturer's defects.







DATE:

	*	
	E	D
3.5W	. an	d 5V

AVAILABLE LED LA							
				_			JOB INFORMATION
LAMP NUMBER	WATTS	BRAND	BEAM SPREAD I	VI LUMEN	COLOR & TEMP.	ORDER CODE	
LAWI NOWIDER	********	DIVAND	OT NEAD	LOWILIA	1 - 1411 .	CODL	TYPE:
L-EDMR16-EP-3W-FL	3.5	<b>EPISTAR</b>	45° Flood	210	WW 2700K	MR16-EP-3W-FL	IOD NAME & ADDDESS.
L-EDMR16-EP-5W-FL	5	EPISTAR	45° Flood	270	WW 2700K	MR16-EP-5W-FL	JOB NAME & ADDRESS:
L-EDMR16-3W-WW-SP	3.5	CREE	15° Spot	210	WW 2700K	MR16-3W-WW-SP	
L-EDMR16-3W-WW-FL	3.5	CREE	45° Flood	210	WW 2700K	MR16-3W-WW-FL	PRODUCT #:
L-EDMR16-3W-WW-WF	3.5	CREE	60° Wide Flood	210	WW 2700K	MR16-3W-WW-WF	TOTAL QUANTITY:
L-EDMR16-5W-WW-SP	5	CREE	15° Spot	270	WW 2700K	MR16-5W-WW-SP	TOTAL QUANTITY.
L-EDMR16-5W-WW-FL	5	CREE	45° Flood	270	WW 2700K	MR16-5W-WW-FL	LAMP TYPE & WATTAGE:
L-EDMR16-5W-WW-WF	5	CREE	60° Wide Flood	270	WW 2700K	MR16-5W-WW-WF	TRANSFORMER:
							CONTRACTOR:
							CONTRACTOR:
							SPECIFIER: