



1633 Staunton Ave Los Angeles, CA 90021

(800) 727-9957 (800) 727-9262 (213) 747-3234

(213) 747-4500

E-Mail: sales@coronalighting.com

## SPECIFICATION SHEET

PRODUCT #: CL-224-AB

•Well Lights

Cast Brass

## **Fixture Specifications:**

Housing: **Cast Brass** 

Finish: AB- Antique Bronze.

Natural toning process. AB finish will vary due to

Lens: Clear, tempered and heat resistant convex glass.

Extra flat lens included.

Socket: Top grade ceramic bi-pin socket with retention

Lamp: 12V, MR-16 halogen, 50W max. L-BAB-C20 (20w)

standard. See below for available LED lamps.

Gasket: Silicone "0" ring seals faceplate to housing

providing weather tight protection.

Wiring: Fixture is prewired with a 3-ft 18-2 SJT-W direct

burial cord. Wire connector available seperately.

Gel filled wire nut CX-854 may be ordered to

Corona Lighting.

Mounting: In-ground direct burial or concrete encasement.


Electrical Notes: A remote 12V transformer required, may be

ordered to Corona Lighting seperately. Voltage range for 12V halogen lamps are 11V-12.5V Voltage range for LED lamps are 9V-17V.

Warranty: Limited lifetime warranty on brass fixture

against manufacturer's defects.







AVAILABLE LED LAMPS  JOB INFORMATION								
LAMP NUMBER	WATTS	BRAND	BEAM SPREAD L	I .UMEN	COLOR & TEMP.	ORDER CODE	TYPE:	DATE:
L-EDMR16-EP-3W-FL L-EDMR16-EP-5W-FL	3.5 5	EPISTAR EPISTAR	45° Flood 45° Flood	210 270	WW 2700K WW 2700K	MR16-EP-3W-FL MR16-EP-5W-FL	JOB NAME & ADDRESS:	DAIL.
L-EDMR16-3W-WW-SP	3.5	CREE	15° Spot	210	WW 2700K	MR16-3W-WW-SP		
L-EDMR16-3W-WW-FL	3.5	CREE	45° Flood	210	WW 2700K	MR16-3W-WW-FL	PRODUCT #:	
L-EDMR16-3W-WW-WF	3.5	CREE	60° Wide Flood	210	WW 2700K	MR16-3W-WW-WF	TOTAL QUANTITY:	
L-EDMR16-5W-WW-SP	5	CREE	15° Spot	270	WW 2700K	MR16-5W-WW-SP	TOTAL QUANTITI.	
L-EDMR16-5W-WW-FL	5	CREE	45° Flood	270	WW 2700K	MR16-5W-WW-FL	LAMP TYPE & WATTAGE:	
L-EDMR16-5W-WW-WF	5	CREE	60° Wide Flood	270	WW 2700K	MR16-5W-WW-WF	TRANSFORMER:	
							CONTRACTOR:	
							SPECIFIER:	