CL-331-6	ЗК		
Product Specification Sheet			
HOUSING:	Die cast aluminum adjustable fixture, suspended inside a reversible flat or angled cut PVC sleeve		
FINISH:	Polyester UV powder coated fixture and PVC sleeve available in BK -Black.		
LENS:	Clear, tempered and heat resistant glass with a silicone gasket.		_ -31"→
	See accessories & parts for special effect lenses, honeycomb louver and frosted glass lens CX-380-FR.	CL-331-BK	CX-854 DIRECT BURIAL WIRENUT AVAILABLE
LAMP TYPE:	12V, MR-16 halogen, 50W max. See lamp guide for LED and color MR-16 lamps.		
MOUNTING:	In-ground direct burial or concrete encasement. Use gravel for proper drainage. Angle cut end required to be installed 3" above the ground.		CORONA
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	8" ↓ 6¼" ⊢ 5½"	Lighting WWW.CORONALIGHTING.COM Tel: 800-727-9262 213-747-4500 Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-16 lamp.
- Remote 12 Volt transformer is required.
 See transformers and accessories for variety of options and choices.