CL-333-E	3K		
Product Specification Sheet			
HOUSING:	Die cast aluminum adjustable fixture, suspended inside a reversible flat or angled cut PVC sleeve		LED AVAILABLE
FINISH:	Polyester UV powder coated fixture and PVC sleeve available in <b>BK</b> -Black.		
LENS:	Clear, tempered and heat resistant glass with a silicone gasket.		¾"  
	See accessories & parts for special effect lenses, honeycomb louver and frosted glass lens CX-380-FR.	CL-333-BK	CX-854 DIRECT BURIAL WIRENUT AVAILABLE
	101/145 101 1 501/	  3 <sup>7</sup> / <sub>8</sub> "	
LAMP TYPE:	12V, MR-16 halogen, 50W max.  See lamp guide for LED and color MR-16 lamps.	41/4" 65/8"	
MOUNTING:	In-ground direct burial or concrete encasement. Use gravel for proper drainage. Angle cut end required to be installed 3" above the ground.	31/4"	CORONA
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	8" 	Lighting  WWW.CORONALIGHTING.COM  Tel: 800-727-9262 213-747-4500  Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-16 lamp.
  Remote 12 Volt transformer is required.
  See transformers and accessories for variety of options and choices.