CL-500	,		
Product Specification Sheet			
HOUSING:	Die-cast aluminum.		Y
FINISH:	Polyester UV powder coated, available in BK -Black, BZ -Bronze, GR -Green, RT -Rust, VG -Verde Green, WH -White.		LED
LENS:	Clear, tempered, and heat resistant glass with silicone gasket. See accessories & parts for special effect lenses, honeycomb louver and frosted	CL-500-BK	CX-839 CORONA UNIVERSAL
	glass lens CX-251-FR.		CONNECTOR AVAILABLE
LAMP TYPE:	12V, MR-16 halogen, 35W max. See lamp guide for LED and color MR-16 lamps.	33/4" 3"	
MOUNTING:	Adjustable cast aluminum knuckle with 1/2" NPT, including ground spike. Wire connector excluded. See accessories & parts for optional mounting hardware.	11/4"	CORONA Lighting WWW.CORONALIGHTING.COM
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	<u> </u>	Tel: 800-727-9262 213-747-4500 Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-16 lamp.Remote 12 Volt transformer is required.
- See transformers and accessories for variety of options and choices.
- When ordering, add the 2 letter color code to the end of the product number.