CL-510			
Product Specification Sheet			$ \hspace{.1cm} $
			IED
HOUSING:	Die-cast aluminum.		AVAILABLE
FINISH:	Polyester UV powder coated, available in VG -Verde Green, BK -Black.		
LENS:	Clear, tempered, and heat		44" \ /~ 44"
	resistant glass with silicone gasket.		11/4"
	See accessories & parts for special effect lenses and honeycomb louver.	CL-510-VG	CX-839 CORONA UNIVERSAL CONNECTOR AVAILABLE
	Honeycomb louver.	٨	
LAMP TYPE:	12V, MR-11 halogen, 35W max.	5" 21/4"	
	land the same good, contraction		
MOUNTING:	Adjustable cast aluminum knuckle with 1/2" NPT, including ground spike. Wire connector excluded.	23/4"	
	See accessories & parts for optional mounting hardware.		CORONA Lighting
WIRING:	Fixture is prewired with a 3-foot pigtail of direct burial cable.	81/2"	WWW.CORONALIGHTING.COM Tol: 800-727-9262 213-747-4500 Fax: 800-727-9957 213-747-3234

- Fixture is supplied with 20W MR-11 lamp.
- Remote 12 Volt transformer is required.
- See transformers and accessories for variety of options and choices.
- When ordering, add the 2 letter color code to the end of the product number.