

# Universal Lighting Systems

**Phone:** (888) 866-4765

**Fax:** (888) 806-5557

**Email:** sales@unvls.com

---

## STL Series

### MATERIAL/FEATURES

- 304 Stainless Steel
- Quick Mount Bracket Allows for mounting without templates
- ETL Approved
- Lifetime Warranty - Stainless Steel Case and IE Core
- 1 Year Warrantyfield replaceable timer module (STL-TM)
- Field replaceable timer module (STL-TM) provides Off, On, Auto (photo cell driven), 1,2,4,6,8 and Hour settings included. STL-TM for useonlywith STL Transformers.
- Remote Mount Phtotcell (STL-PC) with 25' Lead included (wIll not function wihtout PC)

### FINISH

- Muted Stainless Steel

### ELECTRICAL

- 6' Heavy Duty 3 Prong Power Cord
- Terminlas for output adn Photocell
- Primary Side Thermal Protection
- Secondary Side Magnetic Circuit Breakers -
- Fully Epoxy Encapsulated EI Laminated Magnetic Single Core
- Internal Wiring rated to 125° C

### DIMENSIONS

- 4" W x 7" H x 3-1/4" D

### MODELS

- |            |      |            |               |
|------------|------|------------|---------------|
| • STL040SS | 40w  | 12/13 Volt | 3.3 Amps Max  |
| • STL070SS | 70w  | 12/13 Volt | 5.5 Amps Max  |
| • STL150SS | 150w | 12/13 Volt | 12.5 Amps Max |

### APPLICATIONS

1. LED Lighting Systems
2. Water Feature Lighting
3. Small Landscape Lighting Projects

### RESOURCES

- Specification Sheet
- Installation Instructions

- [Catalog Page](#)

[« Prev Image](#)   [Next Image »](#)



STL040SS

[Back to Low Voltage Transformers](#)